



MODEL DDSE40P

PORTABLE DEHUMIDIFIER

40 PINTS

DEHUMIDIFIER



EASY-TO-USE CONTROL PANEL WITH HIGH RESOLUTION DISPLAY
CHOOSE THE IDEAL HUMIDITY LEVEL BY ADJUSTING THE HUMIDISTAT. THE ELECTRONIC CONTROLS ALLOW YOU TO MONITOR RELATIVE HUMIDITY AND TEMPERATURE



AUTO RE-START FUNCTION
AUTOMATIC RE-START
IN CASE OF ELECTRIC SUPPLY
SHORTAGE



DOUBLE SYSTEM FOR REMOVING WATER
WATER TANK OR DRAIN
(3FT HOSE INCLUDED)



• MAXIMUM CAPACITY: 40 PINTS/24H.

• COMPACT AND POWERFUL.

• EASY-TO-USE CONTROL PANEL WITH HIGH RESOLUTION

DISPLAY.

• 24 H TIMER.

• ADJUSTABLE HUMIDISTAT, ROOM THERMOSTAT.

• DRY FUNCTION.

• 3 FAN SPEEDS: ± AUTO MODE.

• ANTI FREEZE FUNCTION: IT ALLOWS OPERATING AT LOW ROOM TEMPERATURE DOWN TO 35,6 °F

• DOUBLE CONDENSE ELIMINATION SYSTEM:

REMOVABLE

WATER TANK OR CONTINUOUS DRAIN (3 FT HOSES INCLUDED).

• WATER TANK WITH WATER LEVEL WINDOW.

• TANK CONTROL SYSTEM: THE APPLIANCE STOPS WHEN THE TANK IS FULL.

• EASY ACCESS WASHABLE AIR FILTER.

• R410 ECO-FRIENDLY REFRIGERANT GAS.

• ENERGY STAR COMPLIANT.

• HANDLES AND CASTORS.

DISCLAIMER: FEATURES AND COLORS ARE SUBJECT TO CHANGE WITHOUT NOTICE. UPDATED: 12/01/2011

RADIADOR ELÉCTRICO DE ACEITE Modelo: CFT1507FB



7 Aletas para distribución de calor

Aleta: 150mm x 580mm

Emisión de calor con bajo consumo energético

Tres ajustes de potencia

Termostato Ajustable

Temporizador programable

Protección contra sobrecalentamiento

Aceite de conducción ecológico

Luces indicadoras de encendido

Capacidad por Contenedor:

1530 40' FT - 1734 40' HQ



Temporizador Programable



Tres Ajustes de Potencia
Termostato Ajustable



Almacenamiento de Cable
Ruedas Giratorias



RADIADOR ELÉCTRICO DE ACEITE Modelo: CFT1507FW



7 Aletas para distribución de calor

Aleta: 150mm x 580mm

Emisión de calor con bajo consumo energético

Tres ajustes de potencia

Termostato Ajustable

Temporizador programable

Protección contra sobrecalentamiento

Aceite de conducción ecológico

Luces indicadoras de encendido

Capacidad por Contenedor:

1530 40' FT - 1734 40' HQ



Temporizador Programable



Tres Ajustes de Potencia
Termostato Ajustable



Almacenamiento de Cable
Ruedas Giratorias





MODEL PAC N120E

AIR TO AIR PORTABLE AIR CONDITIONER



12,000 BTUs

UP TO 450 FT²



NEW DESIGN

WITH A FRESH AND INNOVATIVE DESIGN, PINGUINO PAC N120E GUARANTEES THE MAXIMUM IN TERMS OF COMFORT, ENERGY SAVING AND CARING FOR THE ENVIRONMENT, THANKS TO ITS EFFICIENCY, ITS SILENT OPERATION AND ITS LOW POWER CONSUMPTION. IT **REFRESHES, DEHUMIDIFIES, PURIFIES** THE AIR AND FURNISHES THE HOME. **EASY-TO-USE LED CONTROL**



REMOTE CONTROL

WITH LARGE LCD DISPLAY. IT CONTROLS ALL THE AIR CONDITIONER SETTINGS AND PARAMETERS



R410A REFRIGERANT IS ECOLOGICAL, HUS RESPECTING THE ENVIRONMENT WHILE ENSURING USER COMFORT AND ENERGY EFFICIENCY.



• **MAXIMUM COOLING CAPACITY: 12,000 BTU/H.**
ROOM SIZE UP TO: 450 FT²

• **DEHUMIDIFIES WHILE CONDITIONING.**
(REMOVES 54,95 PINTS/24H. OF EXCESS MOISTURE)

• **DEHUMIDIFYING ONLY FUNCTION**
(REMOVES 86,65 PINTS/24H OF EXCESS MOISTURE)

• **FAN ONLY FUNCTION.**

• **3515 WATTS HEAT PUMP.**

• **3 FAN SPEEDS (INCLUDING QUIET MODE TO ENSURE THE MAXIMUM QUIETNESS).**

• **24H DIGITAL TIMER AND THERMOSTAT.**

• **EXCLUSIVE CONDENSATE RECIRCULATION SYSTEM WITH**

NO DRIP TECHNOLOGY: NO MORE DROPS AND MORE

USER FRIENDLY (NEVER EMPTY A BUCKET AGAIN)

• **HANDLES AND CASTORS.** (UPDATED: 12/04/2011)



DISCLAIMER: FEATURES AND COLORS ARE TENTATIVE AND SUBJECT TO CHANGE WITHOUT NOTICE.

WINDOW BRACKET INCLUDED

PORTABLE AIR CONDITIONER